

LOW PRESSURE AUTOMATIC SPRAY GUN

The DeVilbiss Cobra 3c automatic spray gun is the ideal solution for spraying camera, computer and mobile phone components and many other products.

- *Stainless Steel fluid passageways, sprays water-based and solvent-based paints*
- *Micrometer needle adjustment for fine and accurate fluid flow control*
- *Small, compact gun size weighing just 496g, easy maintenance and dis-assembly*



- *Gun supplied with air and fluid hose fittings. Gun Mounting via 8.2mm round bar (option)*
- *Wide range of proven air caps and fluid tips with hardened tips and needles as standard*
- *Independent fan, atomising and operating air ideal for robot and machine applications*



COBRA 3C
by **DEVILBISS**®

LOW PRESSURE AUTOMATIC SPRAY GUN

Cobra 3c is an automatic low pressure air spray gun (constant air bleed) for the application of solvent and water based paints for use on automatic reciprocator, rotary and robotic painting machines. The gun utilises the world renowned DeVilbiss Trans-Tech or HVLP atomisation technology with hardened fluid tips and needles as standard, to provide excellent paint compatibility on

a wide variety of applications. All fluid passageways in the gun are constructed from high grade stainless steel and the gun uses a micrometer needle adjustment knob for fine and accurate fluid flow control.

The gun requires remotely positioned air valves (not supplied with the gun) to control the air supply for gun triggering, atomisation and fan size adjustment.

COBRA 3C
by **DEVILBISS**®

- Fast maintenance and serviceability
- Quick easy cleaning of external parts and internal passageways
- Air cap indexing for consistent application repeatability (option)
- Fast on/off operation of fluid needle
- Independent fan, atomising and triggering air for total machine compatibility.

Air Cap and Fluid Tip options and part numbers:

Air Cap Type	Part No.	Technology	Air Cap Code
590	SP-100-590-ADV-K	Trans-Tech	COM 590
590 HV	SP-100-590HV-ADV-K	HVLP	590 HV

Fluid Nozzle Size mm	Hardened Fluid Nozzle	Hardened Fluid Needle	Number on Fluid Needle
0.7	SP-259N-07-K	SPA-353-07-K	3C 07
0.85	SP-259N-085-K	SPA-353-085-K	3C 085
1.0	SP-259N-10-K	SPA-353-10-K	3C 10

Product part number example CBA3C-590HV-10N means:

CBA3C = Cobra 3c Automatic Gun
590HV = Air Cap type
10 = 1.0mm fluid tip
N = Hardened fluid tip and needle

Cobra 3c automatic spray guns include air and fluid inlet connections

Specification	Thread	Pressure
Fluid inlet and fluid recirculation	1/8 BSP Female	Max 15 bar / 218 psi
Air inlet Pattern + Length	1/8 BSP Female	Max 12 bar / 174 psi
Cylinder/trigger	1/8 BSP Female	3.5 to 6 bar / 51 to 87 psi
Maximum temperature in use	40°C / 104°F	
Spray gun weight	496g / 17.5 oz	

Materials of construction	
Gun body / Manifold / Micrometer Assembly	303 Stainless steel, 6082 Aluminium Alloy
Tip / Needle	Hardened 303 Stainless steel
Fluid seals	Viton Extreme, Polyethylene

Typical Applications

- Rotary spraying machines
- Reciprocators
- Robotic applicators
- Other automatic spraying machines



For more technical information please refer to the DeVilbiss Cobra 3c Service Bulletin.

Finishing Brands (UK) Limited
Ringwood Road, Bournemouth
Dorset, England BH11 9LH
Tel: +44 (0)1202 571111 Fax: +44 (0) 1202 573488
Email: marketing-uk@finishingbrands.eu

Surfaces et Finitions
163-171 Avenue des Auréats
BP 1453, 26014 Valence cedex FRANCE
Tel: +33(0)4 75 75 27 00 Fax: +33(0)4 75 75 27 59
Email: marketing-fr@finishingbrands.eu

Finishing Brands Germany GmbH
Justus-von-Liebig-Strasse 31
63128 Dietzenbach Germany
Tel: +49 (0) 6074-403-233 Fax: +49 (0) 6074-403-281
Email: marketing-de@finishingbrands.eu