

Spray valve GF/4 and GF/4 HVLP

*Vom Fachmann
• FROM EXPERTS • TO EXPERTS •
für den Fachmann*



schütze

The spray valves of series GF/4 and GF/4 HVLP are pneumatically controlled spray valves. They are suitable for spraying colours, paints, release agents, oils, glues, adhesives and other fluids. Depending on viscosity of fluid different nozzle dimensions are available.

The supply of fluid will be done via pressure tanks or pumps.

These spray valves can be used for continuous or intermitted employments.

A special of the GF/4 is the separate regulation of atomizing air for the cone holes and the middle hole via separate air connections (remote-controlled by external air pressure regulators). In this way the spray angle can be regulated as needed from round spray to approx. 90°-flatspray without changing the air cap.

Also available in HVLP-version (= GF/4 HVLP).

- available nozzle dimensions:
0,3/0,5/0,8/1,0/1,2/1,4/1,5/1,7/2,0/2,5/3,0/
3,5mm Ø
- with ratchet regulator for easy adjusting amount of fluid.
- with clamp for easy adjustment (Ø 12mm)
- continuously adjustable regulation of spray jet from round- to flat spray by external air pressure regulators
- additional material connection available (Option)

Technical data

material pressure	:as needed, max. 10 bar
control air pressure	:min. 3 bar, max. 6 bar
atomizing air pressure	:as required
measurements	:approx. 100 x 63 x 62 mm (incl. connections)
weight	:approx. 400 g
nozzle + needle	:stainless steel
valve body	:aluminum, chemically nickel plated



ALFRED SCHÜTZE Apparatebau GmbH
- Spraytechnology -
Hannoversche Str. 69-71, D-28309 Bremen;
P. O. Box 44 86 48, D-28286 Bremen-Germany
Tel. +49 (4 21) 43 51 00
Fax +49 (4 21) 4 35 10-43
www.schuetze-gmbh.de
info@schuetze-gmbh.de